

## VERIFICATION OF TRANSLATION

I, Kiyoshi Maejima, residing at 4-15, Daitakubo 4-chome, Minami-ku, Saitama-shi, Saitama-ken, Japan, am the translator of the documents attached and I state that the following is a true translation to the best of my knowledge and belief of Description, Claims and Abstract of Japanese Patent Application No. 2002-373540 filed on December 25, 2002.

Dated this *4th* day of *February*, *2008*

Signature of translator

  
Kiyoshi Maejima

【Name of the Document】 Specification

【Title of the Invention】 Tire Structural Member Fabricating  
Method

【Scope of Patent Claims】

【Claims 1】 A tire structural member fabricating method, which fabricates a tire structural member by successively attaching strips to a convex outer surface of a forming drum such that the strips extend obliquely, said method comprising the steps of:

continuously attaching strips to the convex outer surface of the forming drum by successively feeding strips onto the convex outer surface from a forward end of a strip feed means, while the strip feed means is being moved along the center axis of the forming drum relative to the forming drum at a fixed speed; and

controlling the rotation of the forming drum by a controlling means for controlling the rotation of the forming drum such that the angular velocity of the forming drum varies gradually from a minimum angular velocity at a moment a leading end of the strip is attached to the convex outer surface of the forming drum to a maximum angular velocity at a moment the strip is attached to a middle part of the convex outer surface of the forming drum and from the maximum angular velocity to a minimum angular velocity at a moment a trailing end of the strip is attached to the convex outer surface of the forming

drum, the minimum angular velocity at the moment the trailing end is attached being equal to the minimum angular velocity at the moment the leading end is attached.

**【Claims 2】** The tire structural member fabricating method according to claim 1, wherein  $n$  strips of a width  $w$ , which is a dimension transverse to the longitudinal direction of each strip, are successively attached to the convex outer surface of the forming drum to fabricate a tire structural member, comprising the step of:

controlling the rotation of the forming drum so that the forming drum rotates at angular velocity  $\omega$  meeting relation expressed by:

$$\tan^{-1}\left(\frac{r\omega}{V}\right) = \cos^{-1}\left(\frac{nw}{2\pi r}\right)$$

where  $V$  is the fixed speed of the strip feed device,  $r$  is the radius of the convex outer surface of the forming drum as a function of a distance along the center axis of the forming drum by which the strip feed means travels, and  $\omega$  is an angular velocity of the forming drum.

**【Claims 3】** The tire structural member fabricating method according to claim 1 or 2, wherein each of the strips is given opposite oblique ends cut at an angle of  $\cos^{-1}(nw/2\pi r_0)$  to a longitudinal direction of the strip, where  $r_0$  is the radius of the opposite ends of the forming drum.

**【Detailed Description of the Invention】**

【0001】

【Technical Field to which the Invention pertains】

The present invention relates to a tire structural member fabricating method that attaches a plurality of strips successively to the outer surface of a forming drum such that the strips extend obliquely.

【0002】

【Prior Art】

Tire structural members fabricated by a tire structural member fabricating method of this kind include a belt member in the form of a cord-reinforced bias sheet. A belt fabricating method for forming a belt sheet on a cylindrical drum is disclosed in a prior application by the same applicant (refer to Patent Document 1).

【0003】

【Patent Document 1】

JP 2001-88225 A

【0004】

The belt sheet fabricating method disclosed in Patent Document 1 delivers strips successively onto a cylindrical drum rotating at a fixed angular velocity by moving a strip feed means at a fixed speed along the axis of the cylindrical drum to attach the strips to the outer surface of the cylindrical drum obliquely.

【0005】

As shown in Fig. 8-1, a cylindrical belt structure 01 having a cylindrical shape is formed by thus successively attaching the strips to the cylindrical drum in a circumferential arrangement.

【0006】

The cylindrical belt structure 01 is shaped to have an outwardly convex cross section during the shaping process.

【0007】

As shown in Fig. 8-2, stitchers 05 are pressed against end parts of the cylindrical belt sheet 01 so as to reduce the diameter of the end parts to form the convex cylindrical belt structure 02 of a shape conforming to the shape of the outer surface of a green tire.

【0008】

【Underlying Problem to be solved by the Invention】

The thus contracted end parts of the convex cylindrical belt structure 02 are creased and the thickness of the end parts varies along the circumference of the convex cylindrical belt structure 02.

【0009】

The belt sheet fabricating method disclosed in Patent Document 1 attaches the strips to the cylindrical drum. If a convex cylindrical drum having a convex outer surface is used instead of the cylindrical drum, a convex cylindrical belt structure similar to the convex cylindrical belt structure 02

shown in Fig. 8-2 can be formed.

**【0010】**

In a convex cylindrical drum having a curved outer surface of an outward convex cross section, the diameter of a middle part is greater than that of end parts. Therefore, when a predetermined number of strips are attached successively to the convex cylindrical drum such that middle parts of the strips are in properly adjoining disposition, end parts of the strips are overlapped.

**【0011】**

When a predetermined number of strips are attached successively to the convex cylindrical drum such that end parts of the strips are in properly adjoining disposition, gaps are formed between adjacent middle parts of the strips.

In either case, a tire structural member having a uniform quality cannot be formed.

**【0012】**

The present invention has been made in view of such problems and it is therefore an object of the present invention to provide a tire structural member fabricating method capable of fabricating a tire structural member of a uniform quality by successively arranging a plurality of strips so that adjacent strips are in properly adjoining disposition.

**【0013】**

**【Means to solve the Underlying Problem, Effects and**

**Advantages]**

The invention set forth in claim 1 provides a tire structural member fabricating method, which fabricates a tire structural member by successively attaching strips to a convex outer surface of a forming drum such that the strips extend obliquely, the method comprising the steps of continuously attaching strips to the convex outer surface of the forming drum by successively feeding strips onto the convex outer surface from a forward end of a strip feed means, while the strip feed means is being moved along the center axis of the forming drum relative to the forming drum at a fixed speed; and controlling the rotation of the forming drum by a controlling means for controlling the rotation of the forming drum such that the angular velocity of the forming drum varies gradually from a minimum angular velocity at a moment a leading end of the strip is attached to the convex outer surface of the forming drum to a maximum angular velocity at a moment the strip is attached to a middle part of the convex outer surface of the forming drum and from the maximum angular velocity to a minimum angular velocity at a moment a trailing end of the strip is attached to the convex outer surface of the forming drum, the minimum angular velocity at the moment the trailing end is attached being equal to the minimum angular velocity at the moment the leading end is attached.

**[0014]**

Since the angular velocity of the forming drum is increased gradually from the minimum angular velocity at the moment the leading edge is attached to the convex outer surface of the forming roller to the maximum angular velocity at the moment a middle part of the strip is attached to the convex outer surface of the forming roller and from the maximum angular velocity to the minimum angular velocity at the moment the trailing end of the strip is attached to the convex outer surface of the forming drum when the strip feed device moving at the fixed speed relative to the forming drum along the center axis of the forming drum feeds strips successively, the inclination of the strip to the center axis of the forming drum increases gradually from one of the opposite ends of the forming drum toward the middle of the convex outer surface and decreases gradually from the middle part of the convex outer surface toward the other end of the forming drum.

【0015】

Consequently, the width of the strip attached to the convex outer surface of the forming drum in a plane perpendicular to the center axis of the forming drum increases gradually from one of the opposite ends of the forming drum toward the middle of the convex outer surface and decreases gradually from the middle part of the convex outer surface toward the other end of the forming drum. Thus, a tire structural member having a fixed thickness can be fabricated

by successively attaching the predetermined number of the strips to the convex outer surface of the forming drum such that adjacent strips are in proper adjoining disposition and any gap is not formed between middle parts of the adjacent strips. The tire structural member having a fixed thickness improves the quality of a tire.

【0016】

The invention set forth in claim 2 is a tire structural member fabricating method according to claim 1, wherein  $n$  strips of a width  $w$ , which is a dimension transverse to the longitudinal direction of each strip, are successively attached to the convex outer surface of the forming drum to fabricate a tire structural member, comprising the step of controlling the rotation of the forming drum so that the forming drum rotates at angular velocity  $\omega$  meeting relation expressed by  $\tan^{-1}\left(\frac{r\omega}{V}\right) = \cos^{-1}\left(\frac{nw}{2\pi r}\right)$  where  $V$  is the fixed speed of the strip feed device,  $r$  is the radius of the convex outer surface of the forming drum as a function of a distance along the center axis of the forming drum by which the strip feed means travels, and  $\omega$  is an angular velocity of the forming drum.

【0017】

Since a middle part of the convex outer surface of the forming drum bulges outward, the radius  $r$  of the convex outer surface increases from the minimum radius at one of the opposite

ends of the forming drum toward the maximum radius at the middle of the convex outer surface and decreases from the maximum radius to the minimum radius toward the other end. The inclination  $\theta$  of the strip to the center axis of the forming drum is a function of axial distance; that is, the inclination  $\theta$  increases from a minimum inclination at one of the opposite ends of the convex outer surface to a maximum inclination at the middle of the convex outer surface and decreases from the maximum inclination to the minimum inclination toward the other end.

【0018】

Suppose that the strip is inclined at an inclination  $\theta$  on a circle at an axial distance. Then, the length of the strip on the circle is  $w/\cos\theta$ . Therefore,  $n$  times the length is equal to  $2\pi r$ , namely, the circumference of the convex outer surface. Therefore,  $n(w/\cos \theta) = 2\pi r$  and  $\cos\theta = nw/2\pi r$ .

【0019】

When the strip is attached at an inclination  $\theta$  to the circle, the axial speed is  $V$  and the circumferential speed is  $r\omega$ . Therefore  $\tan\theta = r\omega/V$ .

【0020】

Therefore,

$$\tan^{-1}\left(\frac{r\omega}{V}\right) = \cos^{-1}\left(\frac{nw}{2\pi r}\right) (= \theta)$$

When the forming drum is rotated at the angular velocity

meeting the foregoing equation, the strips are attached to the enter convex outer surface of the forming drum such that the end parts of the strips do not overlap and any gap is formed between the middle parts of adjacent strips. Thus a tire structural member having a fixed thickness can be fabricated.

【0021】

The invention set forth in claim 3 is a tire structural member fabricating method according to claim 1 or 2, wherein each of the strips is given opposite oblique ends cut at an angle of  $\cos^{-1}(nw/2\pi r_0)$  to a longitudinal direction of the strip, where  $r_0$  is the radius of the opposite ends of the forming drum.

【0022】

Since the opposite ends of each strip are attached to the opposite ends of the forming drum, respectively, and each strip is given opposite oblique ends cut at an angle of  $\cos^{-1}(nw/2\pi r_0)$  to the longitudinal direction of the strip, the strips can be attached in a smooth circular arc to the forming drum with opposite end parts of the strips properly arranged.

【0023】

【Embodiments of the Invention】

Preferred embodiments of the present invention will be described with reference to Figs. 1 to 7.

A tire structural member fabricating method in a preferred embodiment according to the present invention fabricates a belt sheet 3, namely, a tire structural member,

by successively attaching a plurality of strips 1 to the convex outer surface having a bulging middle part of a forming drum 11 so that the strips 1 extend obliquely.

【0024】

Figs. 1 to 3 show schematic views of a tire structural member fabricating apparatus 10 for carrying out the tire structural member fabricating method.

【0025】

The forming drum 11 has a convex outer surface having an outwardly convex cross section. A peripheral surface of the forming drum 11 has thereon a plurality of electromagnets 12 arranged along the circumference of the forming drum 11.

A servomotor 13 drives the forming cylinder 11 through a belt 14 to rotate the forming roller 11 about its center axis C.

【0026】

A strip attaching device 21 is disposed obliquely above the forming drum 11 to attach strips 1 to the forming drum 11.

A pair of rails 23 is extended in a left-to-right direction parallel to the center axis C of the forming drum 11 on a base 22. A long sliding support plate 25 is supported on sliders 24 that slide along the rails 23. The sliding support plate 25 moves horizontally in the left-right direction.

【0027】

A threaded shaft 26 extending in the left-right direction is engaged in a nut 27 attached to the sliding support plate 25. A servomotor 28 drives the threaded shaft 26 for rotation through a belt 29 to move the sliding support plate 25 in the left-to-right direction.

【0028】

The sliding support plate 25 has its length in the left-to-right direction as viewed in Fig. 1 and slopes down forward, so that the front end of the sliding support plate 25 is at a level lower than that of the back end of the same. The sliding support plate 25 is supported to be slidable in the left-to-right direction, while maintaining an attitude inclined at an angle (to be referred to later as  $\theta_0$ ) to the center axis C of the forming drum 11.

【0029】

A feed plate 30 is placed longitudinally on the sliding support plate 25. Carrier rollers 31 for carrying strips 1 are supported on the feed plate 30. Guide rollers 32 are arranged along the right and the left side of the feed plate 30.

【0030】

The feed plate 30, similarly to the sliding support plate 25, is extended at the angle  $\theta_0$  to the center axis C of the forming drum 11. The carrier rollers 31 and the guide rollers 32 are arranged on and along a path inclined at the angle  $\theta_0$

to the center axis C.

【0031】

The strip 1 to be fed and attached to the forming drum 11 by the feed plate 30 is a member obtained by obliquely cutting a long belt of a width  $w$  formed by coating a plurality of steel cords 2 with rubber in a predetermined length, as shown in Fig. 5. The strip 1 has oblique ends inclined at the angle  $\theta_0$  to its side edges.

【0032】

The strips 1 delivered onto the carrier rollers 31 of the feed plate 30 are guided by the guide rollers 32 and are carried by the rotating carrier rollers 31. The strips 11 are fed successively from the front end of the feed plate 30 onto the top of the forming drum 11 so that their leading ends come into contact first with the forming drum 11 (see Fig. 2).

【0033】

The electromagnet 12 attracts the leading end part of the strip 1 to the outer surface of the forming drum 11 to pull down the strip 1 from the feed table 30. The sliding support plate 25 together with the feed plate 30 moves parallel to the center axis C of the forming drum 11 while the strip 1 is pulled and the forming drum 11 rotates (see Fig.3).

【0034】

In a state where the leading end part of the strip 1 is attached to the forming drum 11, the strip 1 is fed to the

forming drum 11 so that the longitudinal center axis thereof extends at the angle  $\theta_0$  to the center axis C of the forming drum 11, as shown in Fig.2. Consequently, the strip 1 is attached to the outer surface of the forming drum 11 with the leading edge 1a thereof extending parallel to an end surface of the forming drum 11, while the strip 1 is oriented at the angle  $\theta_0$  to the center axis C.

【0035】

The forming drum 11 is rotated at an angular velocity  $\omega$  and the feed plate 30 is moved parallel to the center axis C of the forming drum 11 at a speed V. Consequently, as shown in Fig. 3, the strips 1 successively fed by the feed plate 30 are attached obliquely to the outer surface of the forming drum 1

【0036】

The foregoing strip attaching cycle is repeated to attach a predetermined number of the strips 1 contiguously to the outer surface of the forming drum 11 to form a tire structural member 3 having an outwardly convex cross section as shown in Fig. 4.

【0037】

The tire structural member fabricating apparatus 10 is provided with a controller 40, which controls the two servomotors 13 and 28. The controller 40 controls the servomotor 28 so that the strip feed plate 30 is moved at the

fixed speed  $V$ . The controller 40 controls the servomotor 13 so that the forming drum 11 is rotated at the variable angular velocity  $\omega$  in the following manner.

【0038】

The controller 40 controls the servomotor 13 such that the angular velocity  $\omega$  of the forming drum 11 varies gradually from a minimum angular velocity at a moment the leading end of the strip is attached to the outer surface of the forming drum 11 to a maximum angular velocity at a moment the strip 1 is attached to a middle part of the outer surface of the forming drum 11 and from the maximum angular velocity to a minimum angular velocity at a moment the trailing end of the strip 1 is attached to the outer surface of the forming drum 11. The minimum angular velocity at the moment the trailing end of the strip is attached is equal to the minimum angular velocity at the moment the leading end is.

【0039】

The strip 1 attached to the outer surface of the forming drum 11 is deformed when the angular velocity  $\omega$  of the forming drum 11 is varied as mentioned above, Fig. 6 showing the shape of the thus deformed strip 1 in development.

【0040】

In Fig. 6, the leading end 1a of the deformed strip 1 is aligned with the Y-axis ( $X = 0$ ) and the middle of the leading end 1a is on the origin of the X-Y coordinate system.

The horizontal distance between the leading end 1a and the trailing end 1b of the strip 1 is D. The trailing end 1b extends along a line parallel with the Y-axis and crossing the X-axis at  $X = D$ , and  $X = D/2$  is the abscissa of the center of the strip 1.

【0041】

Suppose that a part of the outer surface of the forming drum 1 at a distance  $x$  ( $X = x$ ) along the center axis C (X-axis) of the forming drum 11 from the leading end 1a of the strip 1 on the Y-axis ( $X = 0$ ) has a radius  $r$  and the forming drum 11 is rotating at an angular velocity  $\omega$  at a moment the strip 1 is attached to the same part of the outer surface of the forming drum 11. Then, the speed  $dY/dt$  along the Y-axis of the strip 1 at  $X = x$  is equal to the circumferential speed  $r\omega$  of the same part of the outer surface of the forming drum 11, and the speed  $dX/dt$  along the X-axis of the strip 1 at  $X = x$  is equal to the fixed speed  $V$ .

【0042】

Therefore, the gradient  $dY/dX$  of the vector sum of the speeds  $dY/dt$  and  $dX/dt$  is  $r\omega/V$ . Therefore,

$$\tan \theta = \frac{r\omega}{V} \quad \dots\dots\dots (1)$$

【0043】

The angle  $\theta$  is the inclination of the strip 1 to the center axis C (X-axis) at a point  $X = x$ . Therefore, the length along

the Y-axis at the point  $X = x$  is  $w/\cos\theta$ .

【0044】

The circumference of a circle on the outer surface of the forming drum 11 at  $X = x$  is  $2\pi r$ . Therefore,  $n(w/\cos\theta)$  is  $2\pi r$  when  $n$  strips 1 are attached to the outer surface of the forming drum 11 so that the strips 1 are arranged in properly adjoining disposition without forming any gap between adjacent strips 1 at the point  $X = x$ . Therefore, the strips 1 are properly arranged when a condition expressed by Expression (2) is satisfied.

$$\cos\theta = \frac{nw}{2\pi r} \quad \dots\dots\dots (2)$$

【0045】

$\theta$  in Expression (1) and  $\theta$  in Expression (2) are same. Therefore, from Expressions (1) and (2),

$$\tan^{-1}\left(\frac{r\omega}{V}\right) = \cos^{-1}\left(\frac{nw}{2\pi r}\right) \quad \dots\dots\dots (3)$$

【0046】

A tire structural member of a fixed thickness can be formed by thus attaching the  $n$  strips 1 to the outer surface of the forming drum 11 in the range of  $0 \leq X \leq D$  so that the strips 1 are arranged in proper adjoining disposition without forming any gap between adjacent strips 1 when the angular velocity  $\omega$  of the forming drum 11 is controlled so as to meet a condition expressed by Expression (3) when the strip 1 is

being attached to a part at the point  $X = x$  of the outer surface of the forming drum 11.

【0047】

The following equation is obtained by substituting Expressions (1) and (2) into an equation:  $\tan^2 \theta = 1/\cos^2 \theta - 1$

$$\left(\frac{r\omega}{V}\right)^2 = \left(\frac{2\pi r}{nw}\right)^2 - 1$$

Expression (4) is obtained by rearranging this equation.

$$\omega = \left\{ \left( \frac{2\pi r}{nw} \right)^2 - \left( \frac{1}{r} \right)^2 \right\}^{1/2} \times V \quad \dots\dots\dots (4)$$

【0048】

A condition expressed by Expression (4) is the same as that expressed by Expression (3). Therefore, the angular velocity  $\omega$  of the forming drum 11 may be controlled so as to meet the condition expressed by Expression (4).

【0049】

Fig. 7 is a graph showing a cross section of the outer surface of the forming drum 11 on an orthogonal coordinate system.

In Fig. 7, distance  $x$  along the center axis C of the forming drum is measured on the horizontal axis and radius  $r$  of the outer surface of the forming drum 11 is measured on the vertical axis. The radius  $r$  is a function of  $x$ , namely,  $r = f(x)$ .

【0050】

Suppose that the radius of the opposite ends respectively at  $x = 0$  and  $x = D$  of the forming drum 11 to which the strip 1 is attached is  $r_0$ . Then,  $f(0) = f(D) = r_0$ . The radius of a circle on the outer surface of the forming drum 11 at  $x = D/2$  is a maximum radius  $f(D/2)$ .

【0051】

The feed plate 30 move in a direction parallel to the X-axis at the fixed speed  $V$ . Therefore, the feed plate 30 that started attaching a strip 1 to a part at  $x = 0$  of the forming drum 11 at  $t = 0$  attaches the strip 1 to a part at  $x = Vt$  at  $t = t$ .

【0052】

Therefore, the radius  $r$  of the outer surface of the forming drum 11 can be expressed by:  $r = f(Vt)$ , namely, a function of time.

Expression (5) is obtained by substituting  $r = f(Vt)$  into Expression (4).

$$\omega = \left\{ \left( \frac{2\pi r}{nw} \right)^2 - \left( \frac{1}{f(Vt)} \right)^2 \right\}^{1/2} \times V \quad \dots\dots\dots (5)$$

Thus, the angular velocity  $\omega$  can be expressed by a function of time  $t$ .

【0053】

The controller 40 controls the servomotor 13 to rotate the forming drum 11 at the angular velocity  $\omega$  calculated by using Expression (5). Consequently, the  $n$  strips 1 can be

successively attached to the outer surface of the forming drum 11 in a proper arrangement to form a high-quality tire structural member of a fixed thickness.

【0054】

Suppose that the opposite ends at  $X = 0$  and  $X = D$  of the forming drum 11 have a radius  $r_0$ . Then, it is known from Expression (2) that the strips 1 can be attached to the forming drum 11 so that the opposite ends of the strips 1 are properly arranged on the opposite ends of the forming drum 11 when the leading end 1a and the trailing end 1b of each strip 1 are cut so as to slope at an angle meeting an equation:  $\cos \theta_0 = nw/2\pi r_0$  to the side edge of the strip 1.

【Brief Description of the Drawings】

【Fig.1】

A schematic side elevation of a tire structural member fabricating apparatus in a preferred embodiment of the present invention.

【Fig.2】

A top view of a part of the tire structural member fabricating apparatus shown in Fig. 1 at an initial stage of a strip attaching cycle.

【Fig.3】

A top view of a part of the tire structural member fabricating apparatus shown in Fig. 1 at a middle stage of a strip attaching cycle.

## 【Fig.4】

A top view of a tire structural member at the completion of a belt sheet.

## 【Fig.5】

A plan view of a strip.

## 【Fig.6】

A development, on an X-Y coordinate system, of a strip attached to a forming drum.

## 【Fig.7】

A diagrammatic view of a convex outer surface of the forming drum on an orthogonal coordinate system.

## 【Fig.8】

A perspective view explaining a conventional ply sheet fabricating method.

## 【Description of Reference Signs】

1...Strip, 2...Steel code, 3...Belt sheet,  
 10...Tire structural member fabricating apparatus, 11...Forming drum with curved outer surface, 12...Electromagnet, 13...Servomotor, 14...Belt,  
 21...Strip attaching device, 22...Base, 23...Rail, 24...Slider, 25...Sliding support plate, 26...Threaded shaft, 27...Nut, 28...Servomotor, 29...Belt,  
 30...Strip feed plate, 31...Carrier roller, 32...Guide roller, 40...Controller.

【Name of the Document】 Abstract

【Abstract】

【Underlying Problem】 To provide a tire structural member fabricating method capable of fabricating a tire structural member of a uniform quality by successively arranging a plurality of strips so that adjacent strips are in properly adjoining disposition.

【Solution Means】

When fabricating a tire structural member by successively and contiguously attaching strips 1 to the convex outer surface having an outwardly convex cross section of a forming drum 11 such that the strips 1 extend obliquely, a strip feed means 21 moves along the center axis C of the forming drum 11 at a fixed speed V and feeds strips 1 successively onto the outer surface of the forming drum 11. A controller 40 controls the rotation of the forming drum 11 such that the angular velocity  $\omega$  of the forming drum 11 varies gradually from a minimum angular velocity at a moment the leading end of the strip 1 is attached to the convex outer surface of the forming drum 11 to a maximum angular velocity at a moment the strip 1 is attached to a middle part of the convex outer surface of the forming drum 11 and from the maximum angular velocity to a minimum angular velocity, equal to the minimum angular velocity at the moment the leading end is attached to the outer surface of the forming drum 11, at a moment the trailing end

of the strip 1 is attached to the convex outer surface of the forming drum 11. A plurality of strips are successively attached to the outer surface of the forming drum 11 in a proper arrangement to form a tire structural member of a uniform quality.

【Selected Figure】 Fig.1